

Section 114000/Food Service Equipment
100% Bidding Specifications

ITEM 1 - WALK-IN COOLER (1 REQ'D)

Bally Refrigerated Boxes Model CUSTOM

8'6" high walk-in cooler per plan configuration, floorless, with white enamel interior, heated vision window, third hinge Super Door and 25' extended probe. 36" high dtp on door and 60" high on exposed exterior. Vertical and horizontal trim to walls and ceiling.

1 ea 2 (-) extra vapor- proof LED light fixtures

ITEM 2 - EVAPORATOR COIL - COOLER (1 REQ'D) <Included>

Bally Refrigerated Boxes Model BLP209MA-S2D

See plans for location and placement of item with reference to adjoining equipment.

ITEM 3 - REMOTE CONDENSER - COOLER (1 REQ'D)

Bally Refrigerated Boxes Model BEZA008H8-HT3D

Preassembled remote medium temperature condensing unit with UL listed stand and cover

ITEM 4 - BUN / SHEET PAN RACK (2 REQ'D)

Advance Tabco Model PR18-3W Dimensions: 63.25(h) x 20.25(w) x 26(d)

Pan Rack, mobile, full height, end loading, 20-1/4"W x 26"D x 63-1/4"H, (18) 18" x 26" sheet pan capacity, slides on 3" centers, open sides, all-welded aluminum construction, 5" swivel casters, NSF

ITEM 5 - COOLER SHELVING UNIT (5 REQ'D)

Metro Model A2448NK3 Dimensions: 48(w) x 24(d)

5 units 24" x 48" four tier epoxy shelving on 74" posts

ITEM 6 - COOLER SHELVING UNIT (1 REQ'D)

Metro Model A2442NK3 Dimensions: 42(w) x 24(d)

unit 24" x 42" four tier epoxy shelving on 74" posts

ITEM 7 - WALK-IN FREEZER (1 REQ'D)

Bally Refrigerated Boxes Model CUSTOM

8'6" high walk-in freezer per plan configuration, with reinforced floor with aluminum diamond tread overlay and interior ramp. With white enamel interior, heated vision window, third hinge Super Door and 25' extended probe. 36" high dtp on door and 60" high on exposed exterior. Vertical and horizontal trim to walls and ceiling.

1 ea 2 extra vapor- proof LED light fixtures, with clear globes

ITEM 8 - EVAPORATOR COIL - FREEZER (1 REQ'D) <Included>

Bally Refrigerated Boxes Model BLP209LE-S2D

See plans for location and placement of item with reference to adjoining equipment.

1 ea KEC Model CUSTOM DLHT

ITEM 9 - SPARE NO. <Spare No.>

ITEM 10 - SPARE NO. <Spare No.>

ITEM 11 - REMOTE CONDENSER - FREEZER (1 REQ'D)

Bally Refrigerated Boxes Model BEZA025L8-HT3D

Preassembled remote low temperature condensing unit with UL listed cover and stand.

ITEM 12 - FREEZER SHELVING UNIT (2 REQ'D)

Metro Model A2442NK3 Dimensions: 42(w) x 24(d)

2 units 24" x 28" four tier epoxy shelving on 74" posts

ITEM 13 - FREEZER SHELVING UNIT (4 REQ'D)

Metro Model A2460NK3 Dimensions: 60(w) x 24(d)

4 units 24" x 60" four tier epoxy shelving on 74" posts

ITEM 14 - CAN RACK (1 REQ'D)

Advance Tabco Model CR10-162M Dimensions: 71(h) x 24.75(w) x 35.13(d)

Can Rack, mobile design with casters, with sloped glides for automatic can retrieval, designed for #10 & #5 cans, aluminum construction, holds (162) #10 cans, or (216) #5 cans

1 ea Model RA-35 Plate Caster with brake, 4" diameter (1 each)

ITEM 15 - DUNNAGE RACK (2 REQ'D)

Metro Model HP2248PD Dimensions: 12(h) x 48(w) x 22(d)

Metro Bow-Tie™ Dunnage Rack, 22" x 48" x 12"H, slotted, with separate polymer tie for joining racks, corrosion proof polymer construction, NSF

ITEM 16 - DRY STORAGE SHELVING (2 REQ'D)

Metro Model A2442NK3 Dimensions: 42(w) x 24(d)

2 units 24" x 42" five tier epoxy shelving on 74" posts

ITEM 17 - HIGH DENSITY SHELVING (1 kt REQ'D)

Cambro Model CSMHDTK10000 Dimensions: 120(h) OR METRO EQUIVALENT

High Density Track Kit, 10', for (3) Camshelving® Premium Series High Density mobile units, includes aluminum raised track, stainless steel leveling feet, and hardware (raised track must be secured at both ends with Camshelving® stationary unit)

3 ea Model CPMU244875V5480 Camshelving® Premium Mobile Starter Unit, 24"W x 48"L x 75"H, 5-tier, withstands temperature -36°F (-38°C) to 190°F (88°C), includes: (5) vented polypropylene shelf plates with Camguard™ antimicrobial protection, (2) pre-assembled post kits (posts constructed of steel with polypropylene exterior), (10) traverses, molded-in dovetails, (2) sets of post connectors, (4) premium swivel casters with total locking brake, 750 lbs. max capacity, speckled gray, NSF

2 ea Model CPU244884V5PKG Camshelving® Premium Starter Unit, 24"W x 48"L x 84"H, 5-tier, withstands temperature -36°F (-38°C) to 190°F (88°C), includes: (5) vented polypropylene shelf plates with Camguard™ antimicrobial protection, (2) unassembled post kits (posts constructed of steel with polypropylene exterior), (10) traverses &

molded-in dovetails, 800 lbs. capacity per shelf /2,000 lbs. max capacity, speckled gray, NSFMetro

ITEM 18 - HAND SINK (5 REQ'D)

Advance Tabco Model 7-PS-90 Dimensions: 42(h) x 17.25(w) x 15.25(d)

Hand Sink, pedestal mounted base, 14" wide x 10" front-to-back x 5" deep bowl, 20 gauge 304 stainless steel, splash mounted faucet, pedal valves with easy access design, basket drain, wall bracket, NSF, cCSAus

ITEM 19 - SPARE NO. <Spare No.>

ITEM 20 - SPARE NO. <Spare No.>

ITEM 21 - SOAP DISPENSER (5 REQ'D) <By Vendor>

By Vendor Model BY VENDOR

Coordinate installation with Item #18, Hand Sink.

ITEM 22 - PAPER TOWEL DISPENSER (5 REQ'D) <By Vendor>

By Vendor Model BY VENDOR

ITEM 23 - WASTE BASKET (5 REQ'D)

Rubbermaid Commercial Products Model FG254300BLA Dimensions: 15.31(h) x 14.5(w) x 10.5(d)

Waste Basket, 28 quart, 14-1/2"W x 10-1/2"D x 15-5/16"H, fire resistant, rounded corners, textured finish, fiberglass, black, CSFM & UL approved.

ITEM 24 - PREP TABLE W/ SINK (1 REQ'D)

Fabricator Model CUSTOM

Fabricated s/s prep table with 20" x 20" x 12" deep prep sink with removable poly board inset with vertical storage, with 20" x 20" s/s drawer, partial s/s undershelf and five inch rear splash per detail FD-1.2 D.

ITEM 25 - DECK MOUNT FAUCET (1 REQ'D)

Fisher Model 3313

Faucet, deck mount, 8" centers, 12" swing spout, lever handles with color coded indexes, 1/2" male inlets, brass, ADA Compliant

ITEM 26 - SPARE NO. <Spare No.>

ITEM 27 - COMMERCIAL WASTE CONTAINER (3 REQ'D)

NIKEC Model BY OTHERS Dimensions: 27.25(h) x 22(w)

ProSave® BRUTE® Container, without lid, 32 gallon.

ITEM 28 - SHELVING, WALL MOUNTED (1 REQ'D)

Advance Tabco Model WS-12-108-16 Dimensions: 10.5(h) x 108(w) x 12(d)

Shelf, wall-mounted, 108"W x 12"D, 1-5/8" bullnose front edge, 1-1/2"H rear up-turn, 16/304 satin finish stainless steel, NSF (units 84" & longer have (3) support brackets)

ITEM 29 - SPARE NO. <Spare No.>

ITEM 30 - SPARE NO. <Spare No.>

ITEM 31 - CAN OPENER (1 REQ'D)

Edlund Model S-11

Can Opener, manual, 16" bar length, dishwasher safe, rust proof, stainless steel, with cast stainless steel base, NSF certified

1 ea 5 year limited warranty

1 ea Model ST-93 Rustproof Can Opener Cleaning Tool, stainless steel bristles and stainless scraper

ITEM 32 - INGREDIENT BIN (5 REQ'D)

Cambro Model IBS20148 Dimensions: 28(h) x 13(w) x 29.5(d)

Ingredient Bin, mobile, 21 gallon capacity, molded polyethylene with sliding cover, S-hook on front (scoop NOT included), (4) 3" heavy duty casters (2 front swivel, 2 fixed), with bin securely attached to base plate, white with clear cover, NSF

ITEM 33 - SPARE NO. <Spare No.>

ITEM 34 - POT RACK (1 REQ'D)

Advance Tabco Model SW-36 Dimensions: 12(h) x 36(w) x 12(d)

Pot Rack, wall-mounted, double bar design, 36"W x 12"D, constructed of 1/4" x 2" stainless steel, includes: (12) plated double pot hooks, NSF

ITEM 35 - 40 QT. MIXER (1 REQ'D)

Globe Model SP40 Dimensions: 51.5(h) x 25.25(w) x 30.5(d)

Planetary Mixer, floor model, 42 qt. (40 liter) capacity, 3-speed (fixed), #12 attachment hub, includes: stainless steel removable bowl guard with built-in ingredient chute, 40 qt. stainless steel bowl, aluminum spiral dough hook, stainless steel wire whip & aluminum flat beater, interlocked bowl lift, gear driven motor, thermal overload protection, front-mounted touchpad controls with 60-minute digital timer & last batch recall, non-slip rubber feet, cast iron body, 2 HP, cord, NSF, cETLus

1 ea 2 year parts & labor warranty

1 ea 208v/60/3-ph, 7.0 amps, NEMA L15-20P

1 ea Model XBTRUCK-40 Bowl Truck, heavy-duty, with handle, for SP40 40 quart mixer

1 ea Model XVSGH Slicer/Shredder/Grater Housing Only, 9", for #12 hub

1 ea Model XPH Plate Holder, for shredder/grater plates

1 ea Model XASP Slicer Plate, adjustable, maximum slice thickness is 1/2"

1 ea Model XSP332 Shredder Plate, 3/32" (2.3 mm)

1 ea Model XSP14 Shredder Plate, 1/4" (6.3 mm)

1 ea Model XSP12 Shredder Plate, 1/2" (12.7 mm)

ITEM 36 - PREP TABLE W/ SINK (1 REQ'D)

Fabricator Model CUSTOM

Fabricated s/s prep table with 20" x 20" x 12" deep prep sink with removable poly board inset with vertical storage, with 20" x 20" s/s drawer, partial s/s undershelf and five-inch rear splash per detail FD-1.2 D.

ITEM 37 - DECK MOUNT FAUCET (1 REQ'D)

Fisher Model 3313

Faucet, deck mount, 8" centers, 12" swing spout, lever handles with color coded indexes, 1/2" male inlets, brass, ADA Compliant

ITEM 38-42 - SPARE NO. <Spare No.>

ITEM 43 - SHELVING, WALL MOUNTED (1 REQ'D)

Advance Tabco Model WS-12-60-16 Dimensions: 10.5(h) x 60(w) x 12(d)

Shelf, wall-mounted, 60"W x 12"D, 1-5/8" bullnose front edge, 1-1/2"H rear up-turn, 16/304 satin finish stainless steel, NSF

ITEM 44 - SOILED DISHTABLE W/ SINK (1 REQ'D)

Fabricator Model CUSTOM

S/s soiled dish table with five-inch-deep scrap sink with slide bar, 2" deep waste trough welded in with removable perforated basket, trough with disposer provision, ten inch rear and right side splash per detail FD-1.2 D.

1 ea Mount control panel mounting bracket for Item #48, DISPOSER.

ITEM 45 - SPARE NO. <Spare No.>

ITEM 46 - DISHTABLE SORTING SHELF (2 REQ'D)

Advance Tabco Model DT-6R-23 Dimensions: 11.25(h) x 62(w) x 18(d)

Sorting Shelf, wall mounted, tubular design, 62"W, accommodates (3) full size dish racks, solid end brackets, stainless steel, KD

ITEM 47 - PRE-RINSE FAUCET ASSEMBLY (1 REQ'D)

Fisher Model 2110-WB

Pre-Rinse Assembly, single-deck dual control valve, with spring action flexible gooseneck, 21" riser, 36" hose, wall bracket & Ultra-Spray™/PLUS spray valve (1.15 gallons per minute @ 60 PSI)

ITEM 48 - DISPOSER (1 REQ'D)

InSinkErator Model SS-200-6-AS101

SS-200™ Complete Disposer Package, trough mount system, 6-5/8" diameter inlet, with #6 collar adaptor for trough installation, 2 HP motor, stainless steel construction, includes syphon breaker, (2) solenoid valves, (2) flow control valves, programmable AquaSaver® Control Center AS-101 with water-saving technology, automatic water saving function, auto reversing, timed run, post flush, adjustable leg kit

1 ea (3) years parts & labor warranty from date of installation

1 ea Standard height disposer body

1 ea 208v/60/3-ph, 3.6 amps

1 ea Model SYPHON STD Syphon breaker standard, 1/2" (11477)

1 ea Model DEJAMWRENCH Dejamming wrench, fits 6-5/8" opening only (Not for use with throat guard) (13993)

ITEM 49 - POT & PAN SHELIVING (1 REQ'D)

Metro Model A2442NK3 Dimensions: 42(w) x 24(d)

1 unit 24" x 42" five tier epoxy shelving on 74" posts, mobile with the following casters:

(2) 5MPGSA

Super Erecta® Cart-Washable Stem Caster, swivel, 5" dia., 1-1/2"W face, 300 lb. capacity, corrosion resistant, flat polyurethane wheel tread, stainless steel bearings, with bumper

(2) 5MPB GSA

Super Erecta® Cart-Washable Stem Caster, swivel (with foot operated brake), 5" dia., 1-1/2"W face, 300 lb. capacity, corrosion resistant, flat polyurethane wheel tread, stainless steel bearings, with bumper

ITEM 50 - WIRE SHELIVING (2 REQ'D)

Metro Model METROSEAL Dimensions: 48(w) x 21(d)

2 units 18" x 60" five tier epoxy shelving on 74" posts, mobile with the following casters:

(4) 5MPGSA

Super Erecta® Cart-Washable Stem Caster, swivel, 5" dia., 1-1/2"W face, 300 lb. capacity, corrosion resistant, flat polyurethane wheel tread, stainless steel bearings, with bumper

(4) 5MPB GSA

Super Erecta® Cart-Washable Stem Caster, swivel (with foot operated brake), 5" dia., 1-1/2"W face, 300 lb. capacity, corrosion resistant, flat polyurethane wheel tread, stainless steel bearings, with bumper

ITEM 51 - DISHWASHER, CONVEYOR TYPE (1 REQ'D)

Champion Model 44 PRO

Pro Series, 44"W rack conveyor dishwasher, Proportional Rinse, Progressive anti-jam drive system, top mounted Prodigy series HMI user interface, Proactive maintenance software, 100 gallons per hour with energy sentinel (idle pump shut-off), (209) racks per hour, single-piece hood design, single-piece stainless steel upper & lower wash arms manifolds, internal removable scrap basket, dual-piece scrap screens, 20" standard vertical clearance which accommodate 18" x 26" sheet pans, full 180° opening leak proof insulated hinged access doors, automatic tank fill, door safety switches, leak-proof ball valve drains, lower front & side enclosure panels, stainless steel heavy gauge construction including base & legs, electric tank heat, 2 HP wash pump, single point machine & booster connection, vent fan control, stainless steel rear manifolds, includes: (1) 20" x 20" peg rack & (1) 20" x 20" flat rack, NSF, cULus, ENERGY STAR®, Made in USA

| | |
|------|--|
| 1 ea | Factory authorized performance test upon equipment start-up. |
| 1 ea | Left-to-right operation |
| 1 ea | 208v/60/3-ph |
| 1 ea | Electric tank heat |
| 1 ea | Electric booster, 70° rise, 21kW, built-in |
| 1 ea | Detergent & Rinse-aid pumps (mounted & inter-wired) |
| 1 ea | Drain water tempering kit (un-mounted) |
| 1 ea | Stainless steel vent cowl with 7" stack & locking damper (set) |
| 1 ea | 20" High hood vertical clearance for sheet pans |

ITEM 52 - PANT LEG DUCT (1 REQ'D)

Fabricator Model CUSTOM

All welded, water tight dish pantleg duct to extend 6" above ceiling with welded s/s trim ring.

ITEM 52.1 - EXHAUST FAN (1 REQ'D)

Captive-Aire Model DU33HFA

ITEM 53 - CORNER CONVEYOR TABLE (1 REQ'D)

Champion Model PRO90

Corner Conveyor Table, 90°

1 ea Model RCT84 Roller Conveyor Table, 84", stationary, unload end, includes limit switch

ITEM 54 - SPARE NO. <Spare No.>

ITEM 55 - RACK DOLLY (7 REQ'D)

Cambro Model CD2020110 Dimensions: 8.25(h) x 22.5(w) x 22.5(d)

Camdolly®, 22-1/2"L x 22-1/2"W x 8-1/4"H (exterior dimensions), without handle, polyethylene construction, (4) 3" heavy duty swivel casters, load capacity 300 lbs., black, NSF

ITEM 56 - THREE (3) COMPARTMENT SINK (1 REQ'D)

Advance Tabco Model 94-43-72-24RL Dimensions: 45(h) x 127(w) x 31(d)

Regaline Sink, 3-compartment, with left & right-hand drainboards, 24" front-to-back x 24"W sink compartments, 14" deep, with 11"H backsplash, stainless steel legs with adjustable left-to-right and front cross rails, 24" drainboards, 1" adjustable bullet feet, 14 gauge 304 stainless steel, overall 32" F/B x 127" L/R, NSF

3 ea Model K-15 Lever Waste Drain, twist handle operated with built in overflow, fits 3-1/2" drain opening, 2" NPT & 1-1/2" IPS outlet connections

3 ea Model K-4 Support Bracket, for lever waste drain handle, (1) support required for each lever drain

ITEM 57 - WALL / SPLASH MOUNT FAUCET (1 REQ'D)

Fisher Model 13269

Faucet, backsplash mount, 8" centers, 12" swing spout, lever handles with color coded indexes, 1/2" NPT male inlets, brass, CSA, ADA Compliant

ITEM 58 - PRE-RINSE FAUCET, WITH ADD ON FAUCET (1 REQ'D)

Fisher Model 34398

Pre-Rinse Unit, wall mount, 8" adjustable centers, with spring action flexible gooseneck, wall bracket, Add-On-Faucet with 12" spout

ITEM 59-63 - SPARE NO. <Spare No.>

ITEM 64 - OVERSHELF W/ POT RACK (1 REQ'D)

Advance Tabco Model PS-15-72 Dimensions: 15(h) x 72(w) x 15(d)

Shelf with Pot Rack, wall-mounted, 72"W x 15"D, 18/430 stainless steel shelf, 2" x 1/4" stainless steel pot rack, includes: (9) plated double pot hooks, NSF

ITEM 65 - OVERSHELF W/ POT RACK (1 REQ'D)

Advance Tabco Model PS-15-36 Dimensions: 15(h) x 36(w) x 15(d)

Shelf with Pot Rack, wall-mounted, 36"W x 15"D, 18/430 stainless steel shelf, 2" x 1/4" stainless steel pot rack, includes: (6) plated double pot hooks, NSF

1 ea Model TA-60 Modification to reduce length to 30"

ITEM 66 - SPARE NO. <Spare No.>

ITEM 67 - FLOOR TROUGH (1 REQ'D)

Advance Tabco Model FTG-748 Dimensions: 4(h) x 48(w) x 7.5(d)

Floor Trough/Water Receptacle, 48"W x 7-1/2"D x 4" deep, 14 gauge 304 stainless steel, includes stainless steel subway grating constructed from 3/16" x 1" bars, removable stainless steel strainer basket, 4" O.D. waste pipe 3"L, pitched towards waste, NSF

1 ea Model FT-6 Modify length or width of trough to 42"

ITEM 68 - FLOOR TROUGH (1 REQ'D)

Advance Tabco Model FTG-784 Dimensions: 4(h) x 84(w) x 7.5(d)

Floor Trough/Water Receptacle, 84"W x 7-1/2"D x 4" deep, 14 gauge 304 stainless steel, includes stainless steel subway grating constructed from 3/16" x 1" bars, 4" O.D. waste pipe 3"L, pitched towards waste, NSF

ITEM 69 - SPARE NO. <Spare No.>

ITEM 70 - SPARE NO. <Spare No.>

ITEM 71 - LOCKER (5 REQ'D)

Winholt Equipment Model WL-66 Dimensions: 78(h) x 12(w) x 12(d)

Lockers, 6-tier, floor mounted, 12"W x 12"D x 78"H (overall), (1) columns, (6) total lockers, 10"W x 12"D x 12"H (compartments size), doors are mesh grid vented, beige finish, fully assembled

ITEM 72 - MOP SINK (1 REQ'D)

Advance Tabco Model 9-OP-20 Dimensions: 10(h) x 25(w) x 21(d)

Mop Sink, floor mounted, 25"W x 21"D x 10"H (overall), 20"W x 16" front-to-back x 6" deep (bowl size), free flow drain with 2" IPS outlet, stainless steel construction, NSF

ITEM 72.1 - SERVICE FAUCET (1 REQ'D)

Advance Tabco Model K-240-X

Service Sink Faucet, wall mount, 8" OC, 6-1/2" spout, with hose thread & pail hook, vacuum breaker spout, wall braced, chrome-plated brass

ITEM 72.2 - SHELVING, WALL MOUNTED (1 REQ'D)

Advance Tabco Model K-245-X Dimensions: 7.5(h) x 24(w) x 8(d)

Special Value Utility Shelf, wall-mounted, 24"W x 8"D, 1-1/2" upturn on rear & sides, (2) mop holders, (3) rag hooks, stainless steel, NSF

ITEM 73 - MOP BUCKET (1 REQ'D)

BY OWNER Model OWNER

Mop Bucket

ITEM 74 - MEAL TRAY DELIVERY CART (3 REQ'D)

Dinex Model DXPTQC2T2D24 Dimensions: 41.92(h) x 53.16(w) x 35.13(d)

TQ Compact Meal Delivery Cart, (2) door, 2-compartment, 41-9/10"H, enclosed, (24) tray capacity, designed to hold multiple tray sizes (12" x 19", 12" x 20", 14" x 18", 15" x 20" & DXRST152003), 4-3/4" tray height spacing, two trays per slide, vertical push handles, vented side panels, gravity locking door with door stop, corner bumpers, (4) 6" Performa casters (2 rigid, 2 swivel with Tech lock brakes) with noise suppression bearing covers, stainless steel construction, NSF, Made in USA

6 ea Model DXPTSDRAIN Floor drain

ITEM 75 - FLATWARE & TRAY CART (1 REQ'D)

Caddy Model T-303 Dimensions: 50.25(h) x 34.5(w) x 22.5(d)

Tray & Silver Caddy, double tier, 34-1/2"W x 22-1/2"D x 50-1/4"H, cutlery housing with front & back folding plastic covers, (8) removable stainless steel pans each 11-1/2" x 6" x 4" deep, shelf capacity (190) trays up to 15" x 20", welded stainless steel construction, 4" swivel casters, NSF

ITEM 76 - BASE STORAGE/DRYING CART (2 REQ'D)

Dinex Model DX1173X50 Dimensions: 73(h) x 19.5(w) x 20.25(d)

TMP® Drying & Storage Cart, holds 50 domes or 100 bases/underliners or Quicktemp® bases, 1" stainless steel tubing frame, 5" casters (2 with brakes) (1173/X50)

2 ea Model DX1173XC10 TMP® Individual Drying Cradle Insert, for 1173 series, 14 gauge uncoated stainless steel (1173/XC10)

ITEM 77 - DOME STORAGE/DRYING CART (2 REQ'D)

Dinex Model DXIRDSD950 Dimensions: 78(h) x 22.5(w) x 22(d)

Dome Storage Rack, 50 dome capacity, for 9" dome covers, 1" square stainless steel tubing frame construction, welded tray slides, 5" casters (IRDSD9/50)

2 ea Model DX10053 Replacement Washrack and Cradle, for 9" domes, stainless steel

ITEM 78 - HOT FOOD SERVING COUNTER / TABLE (1 REQ'D)

Dinex Model DXP4HF Dimensions: 36(h) x 60(w) x 28(d)

DineXpress™ Hot Food Unit, electric, 60"L x 36"H, (4) wells with 1000w element with thermostatically controlled each, mobile, modular design with interlocking mechanism, 14 gauge stainless steel top, 20 gauge stainless steel front & end panels, 18 gauge stainless steel bottom shelf, manifold drains standard, 5" swivel plate casters (2 with brakes), 4kW, NSF, UL

1 ea 208v/60/1-ph, 19.2 amps, 4000 watts, NEMA 6-30P

1 ea Model DXPIND4 Manifold drains to master valve

1 ea Model DXPAUTOFILL Automatic water fill

ITEM 79 - SPARE NO. <Spare No.>

ITEM 80 - SPARE NO. <Spare No.>

ITEM 81 - INDUCTION CHARGER, FOR HEATED BASES (1 REQ'D)

Dinex Model DX1011120RS

SmartTherm™ STS-II Induction Charger, 811 series, countertop, 1 burner, 10 power settings, LED display, automatic standby/shutoff feature, stainless steel exterior, 120v/60/1-ph, NEMA 5-15P, NSF, cETLus

1 ea 2 year parts & labor warranty

10 cs Model DX821003 Base, for Smart-Therm® STS-II induction charger, 9-3/4" dia., plastic, onyx, NSF (12 each per case)

ITEM 82 - MOBILE PLATE AND DISH DISPENSER (1 REQ'D)
Dinex Model DXPIDPH2E0912 Dimensions: 39.88(h) x 17.25(w) x 30.63(d)
Heated Plate Dispenser, enclosed tubular frame, mobile design, two self-elevating dish dispensing tubes, maximum dish size 9-1/8" diameter, 120v/60/1-ph, 1000w, 8.4 amps, 5-15P, CSA (IDPH2E/0912)

ITEM 83 - MOBILE PROOFER CABINET (1 REQ'D)
Vulcan Model VP18 Dimensions: 71(h) x 25.25(w) x 30.75(d)
Proofing Heated Cabinet, mobile, non-insulated, (18) 18" x 26" x 1" sheet pans or (36) 12" x 20" x 2-1/2" steam table pans, fan & air tunnel, includes (10) pair of adjustable tray slides 3" OC, 1/2 gallon water pan, switch can be set to proof or set for heated holding up to 190° F, glass door, stainless steel construction, includes drip trough & removable drip pan, 5" casters; 2 swivel, 2 rigid with locks, 120v/50/60/1-ph, 2.0kW, cord with NEMA 5-20P, cULus, UL EPH
1 ea 10 year warranty on heating elements

ITEM 84 - PLATE CABINET/COUNTER (1 REQ'D)
Fabricator Model CUSTOM
S/s counter with plate cabinet, s/s undershelf, prewired breaker panel housed behind a s/s magnetic swing door

ITEM 85 - DOUBLE OVERSHELF (1 REQ'D)
Fabricator Model CUSTOM
With microwave provision. Mount to item 84 and 78. Mount heat lamp under top shelf.

ITEM 86 - HEAT LAMP (1 REQ'D)
Hatco Model GRA-72 Dimensions: 2.5(h) x 72(w) x 6(d)
Glo-Ray® Infrared Strip Heater, 72" W, standard wattage, tubular metal heater rod, single heater rod housing, aluminum construction, 1275 watts, NSF, CE, cULus, Made in USA
1 ea 120v/60/1-ph
1 ea Model RMB-3D Remote Control Enclosure, (1) toggle switch

ITEM 87 - CONVEYOR TOASTER (1 REQ'D)
Vollrath Model CT2-120350 Dimensions: 13.13(h) x 14.5(w) x 16.5(d)
Conveyor Toaster, horizontal conveyor, all bread types, (350) slices per hour, 1-3/8"H opening, 10-1/2"W belt (2 slice), variable speed control, power saver mode, quartz heaters, stainless steel & aluminized steel construction, 1" adjustable legs, 120v/60/1-ph, 1.6kW, 13.3 amps, cord with NEMA 5-15P, NSF, cULus, Made in USA (model JT1)
1 ea 2 years parts & 1 year labor warranty
1 ea 1 year warranty including labor when performed at authorized service center (heater tube glass damage not covered)

ITEM 88 - MICROWAVE OVEN (1 REQ'D)
ACP Model RCS10TS Dimensions: 13.75(h) x 22(w) x 19(d)
Amana® Commercial Microwave Oven, 1000 watts, 1.2 cu. ft. capacity, medium volume, 4-stage cooking, (5) power levels, (100) memory settings, braille touch pads, non-removable air filter, side hinged door with

tempered glass, accommodates 14" plate, stainless steel interior & exterior, 120v/60/1-ph, 13.0 amps, 15 MCA, 1550 watts (total), NEMA 5-15P, cETLus, ETL-Sanitation
1 ea 3-year limited warranty (1 year full)

ITEM 89 - SPARE NO. <Spare No.>

ITEM 90 - SPARE NO. <Spare No.>

ITEM 91 - CHECK PRINTER (1 REQ'D) <By Owner>
By Owner Model BY OWNER
Check Printer by Owner.

ITEM 92 - WORK TABLE W/ OVERSHELF (1 REQ'D)
Fabricator Model CUSTOM
Flat top, s/s undershelf and 12" wide table-mounted overshelf.

ITEM 93 - BLIXER (1 REQ'D)
Robot Coupe Model BLIXER6 Dimensions: 20.81(h) x 11(w) x 14.44(d)
Blixer® Commercial Blender/Mixer, vertical, 7 liter capacity, stainless steel bowl with handle, stainless steel fine serrated "S" blade assembly, on/off buttons, two speed 1800 & 3600 RPM, 3 HP, 208-240v/60/3-ph, 12.0 amps, NEMA L15-20P, cETLus, ETL-Sanitation

ITEM 94 - SPARE NO. <Spare No.>

ITEM 95 - JUICE DISPENSER (3 REQ'D) <By Vendor>
By Vendor Model BY VENDOR
Juice Dispenser by Vendor.

ITEM 96 - ICED TEA BREWER (3 REQ'D) <By Vendor>
By Vendor Model BY VENDOR
Iced Tea Brewer by Vendor.

ITEM 97 - COFFEE BREWER (3 REQ'D) <By Vendor>
By Vendor Model BY VENDOR
Coffee Brewer by Vendor.

ITEM 98 - ICE MACHINE & DISPENSER, NUGGET STYLE (3 REQ'D)
Follett LLC Model 12CI425A-L Dimensions: 32.5(h) x 16.12(w) x 23.5(d)
Symphony Plus™ Ice & Water Dispenser, countertop, lever dispense, integral ice machine, Chewblet® ice, air-cooled condenser, up to 425 lb. production in 24 hours, 12 lb. storage capacity, Agion® silver-based antimicrobial protection, stainless steel cabinet with accent trim, 115v/60/1-ph, NSF, cETLus
3 ea 3 year parts & labor warranty, additional 2 years compressor warranty (parts only), standard
3 ea 115v/60/1-ph, 11.0 amps, NEMA 5-15P, standard
3 ea Model AF10LBLEGS 4" Leg Kit

ITEM 98.1 - WATER FILTER SYSTEM (3 REQ'D)

Follett LLC Model 00130229 Dimensions: 18.5(h) x 14.25(w) x 6(d)

Water Filter System, standard capacity, (one per ice machine) for Maestro Plus™ ice machines and Symphony Plus™ ice and water dispensers, filtration capacity 3,000 gallons (11,356 liters), NSF (Net Price)

ITEM 99 - UNDERCOUNTER REFRIGERATOR (3 REQ'D)

Continental Refrigerator Model SW27N-U Dimensions: 31.81(h) x 27.5(w) x 31.56(d)

Undercounter Refrigerator, 27"W, 7.4 cu ft capacity, one-section, (1) field rehingeable door, stainless steel front, top & end panels, aluminum interior, 1-3/8" diameter plate casters, front breathing, rear-mounted self-contained refrigeration, R290 Hydrocarbon refrigerant, 1/5 hp, cETLus, NSF, Made in USA, ENERGY STAR®

3 ea Standard warranty: 3 year parts and labor; additional 4 year compressor part

3 ea 115v/60/1-ph, 2.46 amps, cord, NEMA 5-15P

3 ea Door hinged on right

ITEM 100 - BEVERAGE TABLE (1 REQ'D)

Fabricator Model CUSTOM

S/s beverage table with rear flat bar behind #99 refrigerator to allow it to push completely under the table, and provision for #55, five inch rear, left and right side splashes per detail FD-1.2 D.

ITEM 101 - BEVERAGE TABLE (1 REQ'D)

Fabricator Model CUSTOM

S/s beverage table with rear flat bar behind #99 refrigerator to allow it to push completely under the table, and provision for #55, five inch rear and left side splash per detail FD-1.2 D.

ITEM 102 - PREP REFRIGERATOR (1 REQ'D)

Continental Refrigerator Model SW27N12M-FB Dimensions: 40.88(h) x 27.5(w) x 35(d)

Mighty Top Sandwich Unit, Front Breather, 27"W, 7.4 cu ft capacity, one-section, (12) 1/6 size x 4" deep pans with 8" cutting board, (1) field rehingeable door, stainless steel top, front & end panels, aluminum back & interior, 3-3/4" casters, rear mounted self-contained refrigeration, automatic hot gas condensate evaporator, R290 Hydrocarbon Refrigerant, 1/5 hp, cETLus, NSF, Made in USA

1 ea Standard warranty: 3 year parts and labor; additional 4 year compressor part

1 ea 115v/60/1-ph, 2.46 amps, cord, NEMA 5-15P

1 ea Door hinged on right

ITEM 103 - BUSSING UTILITY TRANSPORT CART (3 REQ'D)

Cambro Model BC230110 Dimensions: 34.63(h) x 33.25(w) x 20(d)

Service Cart, open design, (3) shelves, shelf size approximately 20" x 27", polyethylene exterior, 5" casters (2 fixed, 2 swivel, 1 with brake), 500 lb. load capacity, black, NSF

ITEM 104 - TILTING SKILLET BRAISING PAN, GAS (1 REQ'D)

Groen Model BPM-15GA Dimensions: 41.5(h) x 30.5(w) x 39.75(d)

Braising Pan, gas, 15-gallon capacity, 8" deep pan, 35" pan height, IPX6 water rated electronic Advanced controls with digital display, 1 minute to 10 hour timer, 175° - 400°F preset temperatures along with manual setting capability, manual tilt, standard etch marks, faucet bracket, round tubular open leg base, stainless steel construction, bullet feet, electric spark ignition, 65,000 BTU/hr, cCSAus, NSF, IPX6, Made in USA

1 ea (1) year parts & labor, (10) year pan warranty

- 1 ea 115v/60/1-ph, 5.0 amps
- 1 ea Natural gas
- 1 ea Model 176255 Pan Carrier, half size hotel pan capacity, for 15 (without TDO), 30 & 40 gallon models
- 1 ea Model Z091869 Faucet, single pantry, with swing spout

ITEM 104.1 - SAFETY SYSTEM MOVEABLE GAS CONNECTOR (1 REQ'D)

Dormont Manufacturing Model 1650BPQ48

Dormont Blue Hose™ Moveable Gas Connector, 1/2" inside dia., 48" long, covered with stainless steel braid, coated with blue antimicrobial PVC, 1 SnapFast® QD, 1 elbow, 68,000 BTU/hr minimum flow capacity, limited lifetime warranty

ITEM 105 - FLOOR TROUGH (1 REQ'D)

Advance Tabco Model FFTG-1824 Dimensions: 4(h) x 24(w) x 18(d)

Floor Trough, 24"W x 18"D x 4" deep, with fiberglass grating, stainless steel removable strainer basket, 4" O.D. waste pipe 3"L, pitched towards waste, NSF

ITEM 106 - CONVECTION STEAMER (1 REQ'D)

AccuTemp Model E62081D060 Dimensions: 30(h) x 24(w) x 28(d)

(QUICK SHIP) Connectionless Evolution™ Boilerless, Convection Steamer featuring Steam Vector Technology, counter top, electric, holds (6) 12" x 20" x 2-1/2" deep pans, digital Controls, NO water & drain connection required, warranty NOT voided by water quality, NO water filtration required, 6kW, 208/60/1ph, cord with NEMA L6-30P, cULus, UL EPH Classified, Made in USA, ENERGY STAR®

- 1 ea Door hinged on right
- 1 ea Model SNH-11-00 Support Stand, for single Steam'N'Hold™ or Evolution units, standard mounting height: 34-7/8" to bottom, stainless steel, with 5" casters, UL EPH Classified, Made in USA
- 1 ea Model AT1A-3809-1 Drain kit allows a drain to be plumbed to the Evolution™ Steamer or Connectionless Steamer for draining into a floor drain

ITEM 107 - FLOOR FRYER (1 REQ'D)

Vulcan Model LG400 Dimensions: 46.63(h) x 15.5(w) x 29.75(d)

Fryer, gas, 15-1/2" W, free-standing, 45-50 lb capacity, millivolt thermostat controls, twin baskets, legs, stainless steel front top, door & fry tank, 120,000 BTU, CSA Star, CSA Flame, NSF

- 1 ea 5 year limited fry tank warranty
- 1 ea Natural gas
- 1 ea Model MF-1 Portable Fryer Filtration, 110 lb. oil capacity, 8 gallon/minute pump motor, 4' high temperature discard hose, stainless steel mesh filter screen assembly, no paper required (can be used with any manufacturers brand of free standing fryers), 6" casters, 1/3 HP motor/pump
- 1 ea 120v/60/1-ph, 1/3 hp, 5 amps (for MF-1 filter) requires a NEMA 5-15P, 14 gauge oil & grease rated extension cord.
- 1 st Model CASTERS-PLTMNT Set of 4 adjustable casters, 6" overall height, plate mount, (2) with brakes

ITEM 107.1 - BLUE HOSE GAS CONNECTOR KIT (1 kt REQ'D)

Dormont Manufacturing Model 1675KITS48PS

Dormont Blue Hose™ Moveable Gas Connector Kit, 3/4" inside dia., 48" long, covered with stainless steel braid, coated with blue antimicrobial PVC, (1) SnapFast® QD, (1) Swivel MAX®, (1) full port valve, (1) elbow, (1) Snap'N Go, (1) pair Safety Set® with hardware mounting options, limited lifetime warranty

ITEM 108 - RANGE, 60", 6 BURNERS, 24" GRIDDLE (1 REQ'D)

Vulcan Model 60SS-6B24G Dimensions: 58(h) x 60(w) x 34(d)

Endurance™ Restaurant Range, gas, 60", (6) 30,000 BTU burners with lift-off burner heads, (1) 24" manual griddle, 3/4" thick, 4" wide front grease trough, (2) standard oven bases, stainless steel front, sides, backriser & high shelf, fully MIG welded frame, 6" adjustable legs, 278,000 BTU, CSA Flame, CSA Star, NSF

1 ea Natural gas

1 ea Griddle on left side, in lieu of right side

1 ea Note: The griddle being placed on the left will automatically move the 26" oven to the left

1 ea Stainless steel backriser & lift-off high shelf, standard

2 st Model CASTERS-RR4 Casters, 5" (set of 4) (2 with locks) (quantity of 2 required)

ITEM 108.1 - BLUE HOSE GAS CONNECTOR KIT (1 kt REQ'D)

Dormont Manufacturing Model 16100KITS48PS

Dormont Blue Hose™ Moveable Gas Connector Kit, 1" inside dia., 48" long, covered with stainless steel braid, coated with blue antimicrobial PVC, (1) Snap Fast™ QD, (1) Swivel MAX®, (1) full port valve, (1) elbow, (1) pair Safety Set® with hardware mounting options, limited lifetime warranty

ITEM 109 - WORK TABLE W/ HAND SINK (1 REQ'D)

Fabricator Model CUSTOM

S/s worktable with five inch rear and right side splash per detail FD-1.2 D. , s/s undershelf, five inch deep hand sink and 12" high NSF left side splash.

ITEM 110 - DECK MOUNT FAUCET (1 REQ'D)

Fisher Model 3515

Faucet, deck mount, 4" centers, 12" swivel gooseneck spout, lever handles with color coded indexes, 1/2" NPT male inlets, brass, ADA Compliant

ITEM 111 - DOUBLE-DECK CONVECTION OVEN (1 REQ'D)

Vulcan Model VC44GD Dimensions: 70(h) x 40(w) x 42.25(d)

Convection Oven, gas, double-deck, standard depth, solid state controls, electronic spark igniters, 60 minute timer, (5) nickel plated racks per oven, 8" high legs, stainless steel front, top & sides, stainless steel doors with windows, (2) 50,000 BTU, NSF, CSA Star, CSA Flame, ENERGY STAR®

1 ea Natural gas

1 ea (2) 120v/60/1-ph, 15.4 amps total, (2) cords with plugs

1 ea Gas manifold piping included with stacking kit to provide single point gas connection

1 st Casters, set of (4) in lieu of standard legs

ITEM 111.1 - BLUE HOSE GAS CONNECTOR KIT (1 kt REQ'D)

Dormont Manufacturing Model 1675KITS48PS

Dormont Blue Hose™ Moveable Gas Connector Kit, 3/4" inside dia., 48" long, covered with stainless steel braid, coated with blue antimicrobial PVC, (1) SnapFast® QD, (1) Swivel MAX®, (1) full port valve, (1) elbow, (1) Snap'N Go, (1) pair Safety Set® with hardware mounting options, limited lifetime warranty

ITEM 112 - EXHAUST HOOD ASSEMBLY (1 REQ'D)

Captive-Aire Model 6024ND-2-PSP-F

S/S Exhaust Hood with Make-Up Air, 16'10" long O.A., consisting of the following components to be provided by the F.S.E.C. and installed by the Mechanical Contractor:

- Two hood sections
- Stainless Steel Captrate Solo Filter(s)
- Compact Fluorescent lights
- Grease cup
- Exhaust Riser(s)
- Field wrapper (left, front and right sides, as necessary)
- Fire suppression system cabinet located on left side of hood section as shown on plans.
- Prewired electrical package factory installed in utility cabinet for Exhaust fan(s), Supply Fan(s), Audible alarm, Exhaust on in Fire Condition and Lights out in Fire Condition (INCLUDES SPARE WIRING TERMINAL(S) FOR FIELD WIRING TO BUILDING FIRE PANEL AND ELECTRIC EQUIPMENT OFF IN FIRE CONDITION)
- Pre-piped Wet Chemical Fire Suppression System with detection, control head, microswitches and remote pull station.
- PSP supply plenum
- Left and right end quarter end panels

NOTE: Hood permit, hanging hood, hood installation, all ductwork, setting fans and curbs, patching, all electrical field wiring, start-up & balance, gas or electric shutdown for fire hook-up shall be the responsibility of the Mechanical Contractor.

NOTE: Please refer to the Captive-Aire hood detail drawing(s) in the Food Service Equipment set of plans for further details.

ITEM 112.1 - EXHAUST FAN (2 REQ'D)
Captive-Aire Model DU180HFA

ITEM 112.2 - MUA FAN (1 REQ'D)
Captive-Aire Model A2-D.250-20D-MPU

ITEM 113 - FIRE PROTECTION SYSTEM (1 REQ'D)
Captive-Aire Model TANK

Wet chemical fire suppression system, pre-piped into hood(s) with chrome nozzles, pull station, detection, up to 2" electronic gas valve, permit, certification and ONE test.

1 ea Ansul Manual pull station and micro-switches with two sets of normally open and two sets of normally closed contact points.

1 ea Ansul All exposed pipe and fittings shall be chrome plated or stainless steel.

ITEM 114 - WALL FLASHING - HOOD (1 REQ'D)
Fabricator Model CUSTOM

Cover entire wall behind (and adjacent to) the cooking equipment, from top of coved base to the bottom of exhaust hood, and up to 10' high outside foot print of hood.

ITEM 115 - SPARE NO. <Spare No.>

ITEM 116 - REACH-IN REFRIGERATOR (1 REQ'D)

Continental Refrigerator Model 1RN Dimensions: 82.25(h) x 26(w) x 35.38(d)

Refrigerator, reach-in, one-section, 20 cu. ft., self-contained refrigeration, stainless steel front, aluminum interior & ends, standard depth, full-height solid door, cylinder lock, electronic control with digital display,

hi-low alarm, unit comes standard with expansion valve, electric condensate evaporator, R290 Hydrocarbon refrigerant, 1/4 HP, cETLus, NSF, Made in USA, ENERGY STAR®

- 1 ea Standard warranty: 3 year parts and labor; additional 4 year compressor part
- 1 ea 115v/60/1-ph, 5.2 amps, cord, NEMA 5-15P
- 1 ea Door hinged on left
- 1 ea Stainless steel case back including rear grill & concealed drain
- 1 ea 5" Casters

ITEM 117 - ICE MAKER, CUBE-STYLE (1 REQ'D)

Hoshizaki Model KM-660MAJ Dimensions: 28(h) x 22(w) x 27.38(d)

Ice Maker, Cube-Style, 22"W, air-cooled, self-contained condenser, production capacity up to 665 lb/24 hours at 70°/50° (617 lb AHRI certified at 90°/70°), stainless steel finish, crescent cube Style, R-404A refrigerant, 115v/60/1-ph, 15.2 amps, NSF, UL

- 1 ea Warranty: 3-Year parts & labor on entire machine
- 1 ea Warranty: 5-Year parts & labor on evaporator
- 1 ea Warranty: 5-Year parts on compressor & air-cooled condenser

ITEM 117.1 - WATER FILTRATION SYSTEM (1 REQ'D)

Hoshizaki Model H9320-51 Dimensions: 18.4(h)

Water Filtration System, single configuration, 18.4" H (manifold & cartridge)

- 1 ea Warranty: 1-Year on entire water filtration system & replaceable elements
- 1 ea Model H9655-11 Replacement Water Filter Cartridge, each

ITEM 118 - ICE BIN FOR ICE MACHINE (1 REQ'D)

Hoshizaki Model B-300SF Dimensions: 46(h) x 22(w) x 32.5(d)

Ice Bin, 22"W, top-hinged front-opening door, 300-lb ice storage capacity, for top-mounted ice maker, stainless steel exterior, 6" painted flange legs included, protected with H-GUARD Plus Antimicrobial Agent, ETL, ETL-Sanitation

- 1 ea Warranty: 3-Year parts & labor for bin

ITEM 119 - FLOOR TROUGH (1 REQ'D)

Advance Tabco Model FFTG-1224 Dimensions: 4(h) x 24(w) x 12(d)

Floor Trough, 24"W x 12"D x 4" deep, with fiberglass grating, stainless steel removable strainer basket, 4" O.D. waste pipe 3"L, pitched towards waste, NSF

ITEM 120 - BEVERAGE TABLE W/ HANDSINK (1 REQ'D)

Fabricator Model CUSTOM

S/s beverage table with rear flat bar behind #99 refrigerator to allow it to push completely under the table, and provision for #55, five inch deep handsink and five inch rear and left side splash per detail FD-1.2 D, partial s/s undershelf.

ITEM 121 - DECK MOUNT FAUCET (1 REQ'D)

Fisher Model 3515

Faucet, deck mount, 4" centers, 12" swivel gooseneck spout, lever handles with color coded indexes, 1/2" NPT male inlets, brass, ADA Compliant

ITEM 122 - AIR CURTAIN REFRIGERATOR (2 REQ'D)

Dinex Model DXPACR15L Dimensions: 77.25(h) x 26(w) x 36(d)

ACR Air Curtain Refrigerator, one-section, horizontal and vertical air flow, bottom mount self-contained refrigeration, accommodates: (15) 18" x 26" or (30) 14" x 18" trays, stainless steel tray slides, LED display, 270° swing left hinged insulated stainless steel door with reverse feature, rear mounted tubular push handle with donut bumper, non-marking corner bumpers, (4) 5" casters with brakes, stainless steel, 1/2 HP, 120v/60/1-ph, 16 amps, NEMA-5-20P, Made in USA

ITEM 123 - EMERGENCY STORAGE SHELVING (5 REQ'D)

Metro Model A2460NK3 Dimensions: 60(w) x 24(d)

5 units 24" x 60" five tier epoxy shelving on 74" posts

ITEM 124 - HOSE REEL (1 REQ'D)

Fisher Model 29851 Dimensions: 7(w) x 14.38(d)

Hose Reel Assembly, closed reel rinse wall mounted with spray valve, powder coated steel construction, 30 feet of 3/8"ID, 3 ply hose, working pressure of 200 psi, withstands 160° F water temperature, 1/2" NPT Female garden hose inlet

1 ea Model 1801 Reel Rinse Control Unit, valves, gauges and connections are completely enclosed within a stainless steel cabinet, dual check backflow preventer, water hammer silencer, 90° panel lock, padlock hasp & finger latch, 1/2" NPT female inlets & outlets

ITEM 125 - AIR CURTAIN (1 REQ'D)

Bernier Model CHD10-1048A

Commercial Series High Performance Air Curtain, 48" long, unheated, (1) 1/2 hp three speed motor, for door height up to 10-feet high, aluminum housing with white finish, indoor mounting only, cULus, MADE IN USA

1 ea Five year parts warranty

1 ea Model A 120v/60/1-ph

1 ea White aluminum housing

ITEM 126 - MICROWAVE OVEN (2 REQ'D)

ACP Model RCS10TS Dimensions: 13.75(h) x 22(w) x 19(d)

Amana® Commercial Microwave Oven, 1000 watts, 1.2 cu. ft. capacity, medium volume, 4-stage cooking, (5) power levels, (100) memory settings, braille touch pads, non-removable air filter, side hinged door with tempered glass, accommodates 14" plate, stainless steel interior & exterior, 120v/60/1-ph, 13.0 amps, 15 MCA, 1550 watts (total), NEMA 5-15P, cETLus, ETL-Sanitation

2 ea 3-year limited warranty (1 year full)

ITEM 127 - MICROWAVE OVEN, SHELF (2 REQ'D)

Advance Tabco Model MS-24-24 Dimensions: 11(h) x 24(w) x 24(d)

Microwave Shelf, wall-mounted, 24"W x 24"D, stainless steel, NSF